


# LEAD-LINED GENERATOR AND STORAGE CABINET



Larger generator drawer will accommodate the Mallinckrodt Generator with Elution Shield.

The Generator and Storage Cabinet provides hot lab radiation protection without hampering the elution process. The left drawer accommodates top or side loading generators. In addition to the .5" or 1" lead shielding in front, the drawer has .25" lead shielding on the remaining three sides and bottom. A removable drawer top allows generator replacement. Trap doors on the top and sides of this drawer

provide safe access to the generator. The cabinet has two shielded compartments on the right side for storing decaying generators prior to disposal.



Cabinet drawing dimensions can be accessed at [www.biodex.com](http://www.biodex.com).

## SPECIFICATIONS:

Dimensions: 36.5" w x 24" depth x 36.5" h (92.7 x 61 x 92.7 cm)

### Lead Shielding:

Cabinet: .5" (1.3 cm) or 1" (2.5 cm) thick on all six sides

Drawer: .25" thick (.64 cm) on five sides

Dividers: .5" thick (1.3 cm)

Drawer Dimensions: I.D.: 15.5" w x 11.9" depth x 18.2" h (39.4 x 30.2 x 46.2 cm)

Doors and Drawer: Key-locked

Countertop: Stainless steel with 4" backsplash and .5" spillproof lip

Finish: Powder coat

### Weight:

244-181: 1917 lb (869.5 kg)

244-182: 2815 lb (1277 kg)

- 244-181** Cabinet, Generator and Storage, .5" lead.....
- 244-182** Cabinet, Generator and Storage, 1" lead .....