

LOW-ENERGY SHIELDED DECAY DRUM



Available with .125" or .25" shielding. Shown with optional Transport Dolly.

- *Completely shielded*
- *Convenient sliding access door*

The Shielded Decay Drum provides safe handling and storage of radioactive waste material.

A top-loading, sliding port provides fast, safe access. The drum includes three 30-gallon plastic liners.

With two Shielded Decay Drums on hand, a rotation system can be instituted for an even more practical storage and decay process.

The optional dolly simplifies transport of the decay drum.

SPECIFICATIONS:

Dimensions: 30" h x 19.5" dia (76 x 50 cm)

Lead Shielding: .125" (.3 cm) or .25" (.64 cm) lead

Capacity: 30 gal

Weight:

039-284: 160 lb (72 kg) for .125"

039-244: 280 lb (128.8 kg) for .25"

Shipping Weight:

039-284: 238 lb (107 kg)

039-244: 353 lb (160 kg)

039-599 Transport Dolly

Weight: 14 lb (6.4 kg)

039-284 Decay Drum, .125" lead

Includes: Three 039-286 Plastic Liners

039-244 Decay Drum, .25" lead

Includes: Three 039-286 Plastic Liners

Related:

039-599 Dolly, Transport

Replacement:

039-286 Liner, Plastic, 30-gal capacity